

CHANGING THE ALPHA LEVELS OF AN APPLICATION WINDOW TO INDICATE A
STATUS OF A COMPUTING TASK

5

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is related to the following co-
pending applications, which are filed on even date herewith and
incorporated herein by reference:

10

(1) U.S. Patent Application Serial No. ____/____ (Attorney
Docket No. AUS920010513US1);

15

(2) U.S. Patent Application Serial No. ____/____ (Attorney
Docket No. AUS920010514US1);

20

(3) U.S. Patent Application Serial No. ____/____ (Attorney
Docket No. AUS920010515US1);

25

(4) U.S. Patent Application Serial No. ____/____ (Attorney
Docket No. AUS920010517US1);

(5) U.S. Patent Application Serial No. ____/____ (Attorney
Docket No. AUS920010518US1);

30

(6) U.S. Patent Application Serial No. ____/____ (Attorney
Docket No. AUS920010519US1);

(7) U.S. Patent Application Serial No. ____/____ (Attorney
Docket No. AUS920010520US1);

(9) U.S. Patent Application Serial No. ____/____ (Attorney
Docket No. AUS920010522US1);

(11) U.S. Patent Application Serial No. ____/_____
(Attorney Docket No. AUS920010525US1).

BACKGROUND OF THE INVENTION

1. Technical Field:

The present invention relates in general to computer systems and, in particular, to graphical user interfaces. Still more particularly, the present invention relates to changing the alpha levels of a displayable object within a graphical user interface to indicate a status of a computing task.

2. Description of the Related Art:

Most computer systems include multiple types of software for controlling the functions of the computer system. A first type of software is system software (operating systems), which controls the workings of the computer. A second main type of software is applications, such as word processing programs, spreadsheets, databases, and browsers, which perform the tasks for which people use computers. In addition, a computer system may include network software, which enables groups of computers to communicate, and language software, which provides programmers with the tools they need to write programs.

Software contains many instructions typically executed by a processor and other hardware within a computer system. As instructions are executed, the status or progress of multiple parts of the computer system is often monitored. In particular, the status is the condition, at a particular time, of any of numerous elements of computing including, but not limited to, a device, a communications channel, a network station, a software

program, a bit, or another element. A status may be utilized to report on or to control computing tasks.

5 Most operating systems provide a graphical user interface (GUI) for controlling a visual computer environment. The GUI represents programs, files, and options with graphical images, such as icons, menus, and dialog boxes on the screen. Graphical items defined within the GUI work the same way for the user in most software because the GUI provides standard software routines
10 to handle these elements and report the user's actions.

15 A typical graphical object defined by a GUI is a window or other defined area of a display containing distinguishable text, graphics, video, audio and other information for output. A display area may contain multiple windows associated with a single software program or multiple software programs executing concurrently.

20 Often when multiple graphical objects are displayed concurrently, the graphical objects will overlap. The order in which graphical objects are drawn on top of one another onscreen to simulate depth is typically known as the z-order. Typically, those objects at the top of the z-axis obscure the view of those graphical objects drawn below.

25 Monitoring software may be provided for a user to select to display the status of computing tasks within the GUI. In particular, such monitoring software typically utilizes an additional window, overlapping other open windows, for displaying
30 tables of status information. Requiring an additional window to display monitored status information about computing tasks limits the total amount of screen space and may completely obscure the windows for which status information is being received. Further,

typically monitored information is not described in a manner such that it is easily distinguishable from one application window to another.

- 5 Therefore, in view of the foregoing, it would be advantageous to provide a method, system, and program for displaying status information about computing tasks according to each application window, wherein open application windows are not obscured by the display. Further, it would be advantageous to
- 10 display such information status information about computing tasks according to each application window where overlapping windows will not obscure the status information.

40527033-012303

SUMMARY OF THE INVENTION

5 In view of the foregoing, it is therefore an object of the present invention to provide an improved computer system.

It is another object of the present invention to provide an improved graphical user interface.

10 It is yet another object of the present invention to provide a method, system and program for changing the alpha levels of an application window within a graphical user interface to indicate a status of a computer task.

15 According to one aspect of the present invention, an alpha level is determined to represent a status of a non-interactive computing task. A non-interactive task may include, for example, usage of a processor, memory, a sound card, a graphics card, a storage device, and network bandwidth.

20 A transparency of at least a selected portion of a displayable object associated with the non-interactive computing task is graphically adjusted according to the alpha level, such that the status of the non-interactive computing task is
25 displayed according to the associated displayable object. A displayable object may include, for example, an application window, an icon, a video representation, and a graphical representation. In addition to adjusting a transparency of a displayable object to indicate the status of an associated non-
30 interactive computing task, the color of a displayable object may also be adjusted.

5

10

[illegible]

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself
5 however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

10 **Figure 1** depicts one embodiment of a computer system with which the method, system and program of the present invention may advantageously be utilized;

15 **Figure 2** illustrates a graphical representation of a user interface in which alpha levels of applications windows are adjusted to indicate the status of a computing task in accordance with the method, system, and program of the present invention;

20 **Figure 3** depicts a graphical representation of a user interface in which alpha levels of applications windows are adjusted from those depicted in **Figure 2** to indicate the status of a computing task in accordance with the method, system, and program of the present invention;

25 **Figure 4** illustrates a graphical representation of a user interface in which alpha levels of application windows are adjusted to indicate the status of multiple computing tasks in accordance with the method, system, and program of the present invention;

30

Figure 6 illustrates a high level logic flowchart of a process and program for adjusting the transparency levels of application windows according to the status of computing tasks in accordance with the method, system, and program of the present invention.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

5 A method, system, and program for changing the alpha levels of an application window to indicate a status of a computing task are provided. In addition to application windows, the transparency of other displayable objects may be adjusted without effecting the z-order of those displayable objects. A "displayable object" may include text, icons, video, graphics, windows, or other logical graphical representations displayable within a display area. Displayable objects may be hidden or visible. Further, displayable objects may be layered in a z-order. Moreover, a displayable object may utilize a portion of a display area or may extend across the entirety of a display area. A displayable object may or may not include definable boundaries.

10
15
20 A z-order is the order along the z-axis in which displayable objects appear. Through a z-buffering technique, a depth is associated with each displayable object such that each object appears to be set at a particular depth in comparison with other displayable objects. There may be n-levels of layers within the z-order, where multiple displayable objects may be positioned within a particular n-level of the z-order.

25 The z-order may be a result of the order in which a user opens displayable objects onto the display. Alternatively, according to one advantage of the present invention, a user may designate for the z-order to be set according to a particular criteria.

30 Transparency is a graphical feature that is particularly advantageous to the present invention when utilizing a shading characteristic of a window to indicate the status of a computing task. As will be understood by one skilled in the art, by making

a displayable object appear transparent on a computer screen, other displayable objects below the displayable objects are visible through the resource aid. Therefore, by adjusting the transparency of a window, information may be conveyed. Further, the transparency of a displayable object may be adjusted from opaque to totally transparent.

Typically, the transparency attribute is stored with color values in an alpha channel. In the present invention, adjusting the alpha levels of windows corresponds to adjusting transparency attributes stored in the alpha channels. Alpha levels are adjusted according to the status of a computing task.

Then, when calculating the appearance of a given pixel, the graphic processor uses the alpha channel values to determine the pixel's color through a process termed alpha blending. Through alpha blending, the process adds a fraction of the color of the transparent object set by the alpha channel value to the color of the displayable object below. Mixing the colors together gives the appearance that the displayable object below is seen through a layer of the transparent displayable object. In addition to alpha blending, additional shading may be added to create shadows and other graphical images to cue the viewer to the position of the transparent displayable object.

In the present invention, a computing task may be interactive or non-interactive. Interactive computing tasks are those performed in direct response to a user input, such as a keystroke, cursor input, or other. Non-interactive computing tasks are those not performed in direct response to a user input. For example, memory and CPU utilization are not typically performed in direct response to a user input, but are utilized as a function of an application functioning within the computer

5 system. In an example, where a user selects a button associated with an audio function, the interactive computing task is the actual output of the audio in response to the selection while the non-interactive computing tasks include at least usage of a sound card, memory, and CPU.

10 Advantageously, in the present invention, non-interactive computing tasks may include, but are not limited to, use of memory, use of CPUs, number of CPUs utilized, use of graphics cards for two-dimensional (2D) and three-dimensional (3D) graphics, use of a sound card, number of threads, use of storage devices, and net bandwidth. As will be understood by one with skill in the art, additional software, hardware, and network related non-interactive computing tasks may be utilized within the present invention.

15 In the following description, for the purposes of explanation, numerous specific details are set forth to provide a thorough understanding of the present invention. It will be apparent, however, to one skilled in the art that the present invention may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form to avoid unnecessarily obscuring the present invention.

25 HARDWARE OVERVIEW

30 The present invention may be executed in a variety of systems, including a variety of computing systems and electronic devices under a number of different operating systems. In one embodiment of the present invention, the computing system is a portable computing system such as a notebook computer, a palmtop computer, a personal digital assistant, a telephone or other

electronic computing system that may also incorporate communications features that provide for telephony, enhanced telephony, messaging and information services. However, the computing system may also include, for example, a desktop computer, a network computer, a midrange computer, a server system or a mainframe computer. Therefore, in general, the present invention is preferably executed in a computer system that performs computing tasks such as manipulating data in storage that is accessible to the computer system. In addition, the computer system preferably includes at least one output device and at least one input device.

Referring now to the drawings and in particular to **Figure 1**, there is depicted one embodiment of a computer system with which the method, system and program of the present invention may advantageously be utilized. Computer system **10** comprises a bus **22** or other communication device for communicating information within computer system **10**, and at least one processing device such as processor **12**, coupled to bus **22** for processing information. Bus **22** preferably includes low-latency and high-latency paths that are connected by bridges and controlled within computer system **10** by multiple bus controllers.

Processor **12** may be a general-purpose processor such as IBM's PowerPC™ processor that, during normal operation, processes data under the control of operating system and application software stored in a dynamic storage device such as random access memory (RAM) **14** and a static storage device such as Read Only Memory (ROM) **16**. The operating system preferably provides a graphical user interface (GUI) to the user. In a preferred embodiment, application software contains machine executable instructions that when executed on processor **12** carry out the

operations depicted in the flowcharts of **FIG. 6** and others described herein. Alternatively, the steps of the present invention might be performed by specific hardware components that contain hardwire logic for performing the steps, or by any combination of programmed computer components and custom hardware components.

The present invention may be provided as a computer program product, included on a machine-readable medium having stored thereon the machine executable instructions used to program computer system **10** to perform a process according to the present invention. The term "machine-readable medium" as used herein includes any medium that participates in providing instructions to processor **12** or other components of computer system **10** for execution. Such a medium may take many forms including, but not limited to, non-volatile media, volatile media, and transmission media. Common forms of non-volatile media include, for example, a floppy disk, a flexible disk, a hard disk, magnetic tape or any other magnetic medium, a compact disc ROM (CD-ROM), a digital video disc-ROM (DVD-ROM) or any other optical medium, punch cards or any other physical medium with patterns of holes, a programmable ROM (PROM), an erasable PROM (EPROM), electrically EPROM (EEPROM), a flash memory, any other memory chip or cartridge, or any other medium from which computer system **10** can read and which is suitable for storing instructions. In the present embodiment, an example of non-volatile media is storage device **18**. Volatile media includes dynamic memory such as RAM **14**. Transmission media includes coaxial cables, copper wire or fiber optics, including the wires that comprise bus **22**. Transmission media can also take the form of acoustic or light waves, such as those generated during radio wave or infrared data communications.

Moreover, the present invention may be downloaded as a computer program product, wherein the program instructions may be transferred from a remote computer such as a server **39** to requesting computer system **10** by way of data signals embodied in a carrier wave or other propagation medium via a network link **34** (e.g., a modem or network connection) to a communications interface **32** coupled to bus **22**. Communications interface **32** provides a two-way data communications coupling to network link **34** that may be connected, for example, to a local area network (LAN), wide area network (WAN), or as depicted herein, directly to an Internet Service Provider (ISP) **37**. In particular, network link **34** may provide wired and/or wireless network communications to one or more networks.

ISP **37** in turn provides data communication services through the Internet **38** or other network. Internet **38** may refer to the worldwide collection of networks and gateways that use a particular protocol, such as Transmission Control Protocol (TCP) and Internet Protocol (IP), to communicate with one another. ISP **37** and Internet **38** both use electrical, electromagnetic, or optical signals that carry digital or analog data streams. The signals through the various networks and the signals on network link **34** and through communication interface **32**, which carry the digital or analog data to and from computer system **10**, are exemplary forms of carrier waves transporting the information.

Further, multiple peripheral components may be added to computer system **10**. For example, an audio output **28** is attached to bus **22** for controlling audio output through a speaker or other audio projection device. A display **24** is also attached to bus **22** for providing visual, tactile or other graphical representation

formats. Display **24** may include both non-transparent surfaces, such as monitors, and transparent surfaces, such as headset sunglasses or vehicle windshield displays.

5 A keyboard **26** and cursor control device **30**, such as a mouse, trackball, or cursor direction keys, are coupled to bus **22** as interfaces for user inputs to computer system **10**. Keyboard **26** and cursor control device **30** can control the position of a cursor positioned within a display area of display **24**. It should be
10 understood that keyboard **26** and cursor control device **30** are examples of multiple types of input devices that may be utilized in the present invention. In alternate embodiments of the present invention, additional input and output peripheral components may be added.

15 ALPHA LEVELS CORRESPONDING TO STATUS CONTEXT

20 With reference now to **Figure 2**, there is depicted a graphical representation of a user interface in which alpha levels of applications windows are adjusted to indicate the status of a computing task in accordance with the method, system, and program of the present invention. As illustrated, a user interface **50** includes applications windows **52** and **62**.

25 According to one advantage of the present invention, selected portions of each application window or other displayable object may be adjusted in transparency. In the present example, window **52** is 100% transparent. However, the border of window **52**, text block **54** and selectable buttons **56** and **58** are not adjustable
30 in transparency. Therefore, portions of window **62** that are overlapped by window **52** are visible through the transparent portions of window **52**.

Preferably, a transparency of each window adjusts according to the status of a non-interactive computing task associated with each window. For example, in the present example, if the computing task being measured is graphics card usage, then the transparency of window 52 adjusts to represent no usage of the graphics card while window 62 remains opaque to represent a level of usage. While in the present example the same computing tasks are depicted in multiple windows by transparency levels, in alternate embodiments, alternate computing tasks may be depicted in multiple windows by transparency levels. For example, a transparency of window 52 may adjust according to the status of an installation application during an installation process.

As a further advantage of the present invention, although not depicted, the transparency of window 62 may oscillate according to a frequency spectrum for the sound intended for generation in association with the window. By oscillating the transparency of a window according to the frequency spectrum of sound, a visual cue is provided to a user of the sound intended for generation in association with the window.

The present invention is particularly advantageous because the status of computing tasks associated with multiple windows are viewable concurrently independent of whether a window is active or not. In addition, as depicted in the present example, the present invention is advantageous where a single computing task is utilized to adjust transparency in all open windows, because the window utilizing the most resources is typically most visible without adjusting the z-order of the windows.

Referring now to **Figure 3**, there is illustrated a graphical representation of a user interface in which alpha levels of applications windows are adjusted from those depicted in **Figure 2** to indicate the status of a computing task in accordance with the method, system, and program of the present invention.

According to one advantage of the present invention, the transparency of windows adjusts over time as the status of non-interactive computing tasks adjust. In the present example, the transparency of window **52** is adjusted to 80% transparency to represent usage of the sound card in association with window **52**. In addition, in the present example, the transparency of window **62** is adjusted to 50% transparency to represent a shift in sound card usage when compared to the transparency associated with window **62** in **Figure 2**.

With reference now to **Figure 4**, there is depicted a graphical representation of a user interface in which alpha levels of application windows are adjusted to indicate the status of multiple computing tasks in accordance with the method, system, and program of the present invention.

According to one advantage of the present invention, multiple transparency levels may be depicted within multiple sections of a single window, wherein each transparency level is associated with a separate computing task. In the present example, window **52** is divided into sections **64** and **66**, wherein the transparency levels of sections **64** and **66** are each associated with a separate computing task. For example, the transparency level of section **64** may be associated with memory usage while the transparency level of section **66** may be associated with CPU usage.

As illustrated, the portion of window **62** overlapped by window **52** is adjusted in transparency according to the transparency levels of sections **64** and **66**. In the present example, a single computing task is depicted by a transparency level with window **62**, however in alternate embodiments, multiple computing tasks may be illustrated by multiple transparency levels within window **62**.

Advantageously, a user may initiate, by keystroke, voice command or other input sequence, a legend for the computing tasks being depicted by transparency levels within each window. In one embodiment, the transparency level of window **62** may continue to represent sound card usage, as described in Figures **1** and **2**. Alternatively, the transparency level of window **62** may adjust from representing one computing task to representing another computing task.

Referring now to **Figure 5**, there is depicted a graphical representation of selectable transparency preferences set by a user in accordance with the method, system, and program of the present invention. As illustrated, multiple categories may be provided for a user to specify transparency preferences.

In the present example, categories include, but are not limited to, graphical objects **82**, non-computing tasks **84**, transparency level ranges **86**, and colors **88**. Advantageously, a user may specify graphical objects **82** according to windows, icons and other displayable objects or may designate a preference for all displayable objects.

In addition, a user may select from multiple selectable buttons to adjust the current transparency preferences. Selectable buttons include, but are not limited to, editing selection **72**, adding selection **74**, and deleting selection **76**. In response to a selection of editing selection **72**, a user is preferably enabled to edit current and past preferences. In response to a selection of adding selection **74**, a user is preferably enabled to add a new preference. In response to a selection of deleting selection **76**, a user is preferably enabled to delete a current preference.

With reference now to **Figure 6**, there is illustrated a high level logic flowchart of a process and program for adjusting the transparency levels of application windows according to the status of computing tasks in accordance with the method, system, and program of the present invention. As depicted, the process starts at block **90** and thereafter proceeds to block **92**.

Block **92** depicts a determination as to whether or not the status of a non-interactive computing task associated with a window is detected. If a status is not detected, then the process iterates at block **92**. If a status is detected, then the process passes to block **94**.

Block **94** illustrates determining an alpha level for association with the status of the computing element. Next, block **96** depicts determining a color level for association with the particular computing element. Thereafter, block **98** illustrates graphically adjusting the transparency according to the alpha level and color according to the color level of at least a particular portion of the window associated with the computing element; and the process ends.

While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.

5

11/11/92 10:00 AM